




# Flexible Connector Type FF/RED Reducing/Increasing Sizes CS Plate Flange Ends



**Typical Specification:**

Provide, where indicated, a flexible connector consisting of 300 series stainless steel corrugated hose surrounded and supported by 300 series stainless steel braid. End fittings are to be carbon steel 150# drilled plate flange ends and integral Sch 40 concentric reducers. Connector to be \_\_\_\_ inches nominal pipe size by \_\_\_\_ inches nominal reducing size by \_\_\_\_ inches overall length; **Thermo Tech model FF/RED or equal.**

**Notes:**

Special end fittings, lengths, and pressure ratings are available.

Maximum working pressure is based on non-shock service at 70°F.

This connector dampens vibration and accommodates 1/8" lateral offset.

Reducing sizes not shown are Specials. Please consult factory.

NOMINAL PIPE SIZE INCHES	REDUCING PIPE SIZE INCHES			OVERALL LENGTH INCHES	HOSE & BRAID WORKING PRESSURE PSIG
2"	1 ½	1 ¼		12	455
2 1/2"	2	1 ½		12	345
3"	2 ½	2	1 ½	14	295
4"	3	2 ½	2	14	235
5"	4	3		16	205
6"	5	4	3	16	195
8"	6	5	4	18	185
10"	8	6		20	175
12"	10	8	6	22	165
14"	12	10		26	150
16"	14	12		27	110

Job \_\_\_\_\_

Contractor \_\_\_\_\_

Engineer \_\_\_\_\_

Representative \_\_\_\_\_

Order No. \_\_\_\_\_ Date \_\_\_\_\_

Submitted by \_\_\_\_\_

Approved by \_\_\_\_\_ Date \_\_\_\_\_

Tag \_\_\_\_\_



287 South Sante Fe Drive  
Denver, Colorado 80223  
Phone (303) 698-9988  
www.thermotechdenver.com

**Flexible Connector  
Type FF/RED**